

Q UVC-G6-Pro-360

Switching

WiFi

Camera Security

Door Access

Integrations

Advanced Hosting



Dome & Turret > [G6 Pro 360](#)

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

Dimensions	Ø147 x 65.5 (Ø5.8 x 2.6")
IR Night Vision	15m (50 ft) Smart IR (4x controllable zones)
Smart Detections (People, Vehicles, Animals)	✓
Resolution	12MP
Field of View	H: 180°, V: 180°, D: 180°
Audio	Two-way audio
Weatherproofing	IP66
Tamper Resistance	IK10
Mounting	Surface Mount (Included) AI 360 Junction Box, Camera Dual Mount, Arm Mount (Optional)

Performance

Networking Interface 10/100 MbE RJ45 port

Video

Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR
Max. Frame Rate	24 FPS
Resolution	12MP 3504 x 3504 (1:1)
Optics	
Sensor	1/1.6" 12MP
Lens	Fisheye lens
Night Mode	Built-in IR LED illumination and IR cut filter
^ Hardware	
Max. Power Consumption	7.14W
Supported Voltage Range	37—57V DC
Power Method	PoE+
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	610 g (1.3 lb)
Enclosure Material	Aluminum alloy, polycarbonate
Mount Material	Polycarbonate
Expansion Slot	MicroSD card
Button	(1) Factory-reset
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

Stay in Touch



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.